

9606061 | Standard machine tap HSSE-PM -M -DIN 374/376 -C Shape -6H -Dulofix shank


Tap (sintered steel) for steel, aluminium alloys, plastics and composites.



- Especially for aluminium
- Precise and long-lasting thread tapping
- Made in Spain

- Spiral flute

Machine



Application

N 1.1	N 1.2	N 1.3	N 1.5	N 1.6	N 1.7	N 3
N1-1- Aluminum-Series 1000 Alloy: Pure	N1-2- Aluminum-Series 2000 Alloy: with copper	N1-3- Alloy based on aluminum-series 3000: with manganese	N1-5- Aluminum-Series 5000 Alloy: with magnesium	N1-6- Alloy-based aluminum-series 6000: with magnesium and silicon	N1-7- Aluminum-Series Alloy 7000: With Zinc	N3- Copper alloy

Features



Properties and benefits

- + Spiral flute : A flute shape that allows chips to be evacuated through the entrance to the hole. ➡ Allows better heat resistance due to better chip evacuation. For blind holes.



Code	EAN	Thread	Ø	Pitch	Norm	Drill	L	I	I4	I5	QTY	PCB
960606100800125	8420609324628	M 8	8	1,25	DIN 376	6,75	90	18	2-2.5	4,90	1	1
960606101000150	8420609324666	M 10	10	1,5	DIN 376	8,50	100	20	2-2.5	5,50	1	1
960606101200175	8420609324703	M 12	12	1,75	DIN 376	10,25	110	22	2-2.5	7,00	1	1