


1623352	Ø	P	L	l1	d	Limit	□	●Ø
16233521757020	3/8"	24	3.94	.55	.3810	2B	.286	Q
16233521757032	7/16	20	3.94	.59	.3230	2B	.242	W
16233521757036	1/2"	20	3.94	.63	.3670	2B	.275	29/64
16233523474080	5/8"	18	3.94	.75	.4800	2B	.360	37/64
16233523474088	3/4"	16	4.33	.59	.5900	2B	.442	11/16
16233523474096	1"	12	5.51	1.03	.8000	2B	.600	59/64



M
Metric
Métrique
Métrica





ASME B1.13M Norm
Norme ASME B 1.13M
Norma ASME B1.13M

MACHINE CUTTING TAP
TARAU MACHINE À COUPE
MACHO DE CORTE A MÁQUINA


6H **ANSI DIN** **HSS E** **TiAIN COATED**




2,5xd **SEMI BOTTOM**



1603352	Ø	P	L	l1	d	Limit	□	●Ø
16033523474400	M4	0,7	2.48	.24	.1680	6H	.131	0,13
16033523474404	M5	0,8	2.76	.35	.1940	6H	.152	0,17
16033523474408	M6	1	3.15	.43	.2550	6H	.191	0,20
16033523474412	M8	1,25	3.55	.47	.3180	6H	.238	0,27
16033523474420	M10	1,5	3.94	.55	.3810	6H	.286	0,33
16033523474444	M12	1,75	4.33	.63	.3670	6H	.275	13/32
16033523474452	M14	2	4.33	.71	.429	6H	.322	0,47
16033523474460	M16	2	4.33	.75	.4800	6H	.360	0,55



UNC UNF
Normal series American Unified Thread
Filet Unifié Américaine série normal
Rosca Unificada Americana serie normal





ASME B 1.1 Norm
Norme ASME B 1.1
Norma ASME B 1.1

ROLL FORM TAP
TARAU À REFOULER
MACHO DE LAMINACIÓN


2B 3B **ANSI DIN** **HSS E** **TiN COATED**



2,5xd **SEMI BOTTOM**



1623362	Ø	P	L	l1	d	Limit	□	●Ø
16233621745060	#4	40	2.21	.43	.1410	2B	.110	#39
16233621765062	#6	32	2.21	.47	.1410	2B	.110	1/8
16233621765064	#8	32	2.48	.51	.1680	2B	.131	#35
16233621765066	#10	24	2.76	.59	.1940	2B	.152	11/64
16233621765070	1/4"	20	3.15	.67	.2550	2B	.191	#1
16233621765074	5/16	18	3.55	.79	.3180	2B	.238	0,29
16233621765078	3/8"	16	3.94	.87	.3810	2B	.286	S
16233621765090	7/16	14	3.94	.87	.3230	2B	.242	13/32




1623362	Ø	P	L	I1	d	Limit	□	●Ø
16233621765094	1/2"	13	4.33	.98	.3670	2B	.275	0,46
16233621765098	5/8"	11	4.33	1.06	.4800	2B	.360	0,58
16233621765102	3/4"	10	4.92	1.18	.5900	2B	.442	45/64
16233621765106	1"	8	6.30	1.42	.8000	2B	.600	15/16

1623362	Ø	P	L	I1	d	Limit	□	●Ø
16233621765068	#10	32	2.76	.51	.1940	2B	.152	21
16233621765072	1/4"	28	3.15	.67	.2550	2B	.191	#16
16233621765076	5/16	24	3.55	.67	.3180	2B	.238	M
16233621765080	3/8"	24	3.94	.71	.3810	2B	.286	T
16233621765092	7/16	20	3.94	.87	.3230	2B	.242	0,41
16233621765096	1/2"	20	3.94	.87	.3670	2B	.275	0,47
16233621765100	5/8"	18	3.94	.87	.4800	2B	.360	0,60
16233621765104	3/4"	16	4.33	.98	.5900	2B	.442	23/32
16233621765108	1"	12	5.51	1.10	.8000	2B	.600	15/16



M Metric
Metrique
Métrica



ASME B1.13M Norm
Norme ASME B 1.13M
Norma ASME B1.13M

ROLL FORM TAP
TARAUO Á REFOULER
MACHO DE LAMINACIÓN

6H

**ANSI
DIN**

**HSS
E**



**TiN
COATED**



2,5xd



**SEMI
BOTTOM**



1603362	Ø	P	L	I1	d	Limit	□	●Ø
16033621765250	M4	0,7	2.48	.51	.1680	6H	.131	0,14
16033621765252	M5	0,8	2.76	.59	.1940	6H	.152	#13
16033621765254	M6	1	3.15	.67	.2550	6H	.191	#2
16033621765256	M8	1,25	3.55	.79	.3180	6H	.238	M
16033621765258	M10	1,5	3.94	.87	.3810	6H	.286	U
16033621765272	M12	1,75	4.33	.98	.3670	6H	.275	7/16
16033621765276	M14	2	4.33	1.02	.429	6H	.322	33/64
16033621765280	M16	2	4.33	1.06	.4800	6H	.360	19/32

