


1623176	Ø	P	L	I1	d	Limit	□	●Ø
16231761010900	#10	32	2.38	.88	.1940	H3	.152	#21
16231761010401	1/4"	28	2.50	1.00	.2550	H3	.191	#3
16231761010405	5/16	24	2.72	1.13	.3180	H3	.238	I
16231761010409	3/8"	24	2.94	1.25	.3810	H3	.286	Q
16231761010413	7/16	20	3.16	1.44	.3230	H3	.242	W
16231761010417	1/2"	20	3.38	1.66	.3670	H3	.275	29/64



M
Metric
Métrique
Métrica





ASME B1.13M Norm
Norme ASME B 1.13M
Norma ASME B1.13M


MACHINE CUTTING TAP
TARAUO MACHINE Á COUPE
MACHO DE CORTE A MÁQUINA




6H **ANSI** **HSS** **BRIGHT UNCOATED**

1,5xd **PLUG**











1603176	Ø	P	L	I1	d	Limit	□	●Ø
16031761012920	M3	0,5	1.94	.63	.1410	D3	.110	0,10
16031761012922	M3.5	0,6	2.00	.69	.1410	D4	.110	0,21
16031761012923	M4	0,7	2.13	.75	.1680	D4	.131	0,13
16031761012925	M5	0,8	2.38	.88	.1940	D4	.152	0,17
16031761012926	M6	1	2.50	1.00	.2550	D5	.191	0,20
16031761012928	M8	1,25	2.72	1.13	.3180	D5	.238	0,27
16031761012930	M10	1,5	2.94	1.25	.3810	D6	.286	0,33
16031761012932	M12	1,75	3.38	1.66	.3670	D6	.275	13/32



**M**Metric
Métrique
MétricaASME B1.13M Norm
Norme ASME B 1.13M
Norma ASME B1.13M**MACHINE CUTTING TAP**
TARAUD MACHINE À COUPE
MACHO DE CORTE A MÁQUINA**6H****ANSI****HSS****BRIGHT UNCOATED****1,5xd****BOTTOM**

1603176	Ø	P	L	l1	d	Limit	□	●Ø
16031761012940	M3	0,5	1.94	.63	.1410	D3	.110	0,10
16031761012942	M3.5	0,6	2.00	.69	.1410	D4	.110	0,21
16031761012943	M4	0,7	2.13	.75	.1680	D4	.131	0,13
16031761012945	M5	0,8	2.38	.88	.1940	D4	.152	0,17
16031761012946	M6	1	2.50	1.00	.2550	D5	.191	0,20
16031761012948	M8	1,25	2.72	1.13	.3180	D5	.238	0,27
16031761012950	M10	1,5	2.94	1.25	.3810	D6	.286	0,33
16031761012952	M12	1,75	3.38	1.66	.3670	D6	.275	13/32

1 - 2 hls

**UNC UNF**Normal series American Unified Thread
Filet Unifié Américaine série normal
Rosca Unificada Americana serie normalASME B 1.1 Norm
Norme ASME B 1.1
Norma ASME B 1.1**MACHINE CUTTING TAP**
TARAUD MACHINE À COUPE
MACHO DE CORTE A MÁQUINA**2B 3B****ANSI****HSS****BRIGHT UNCOATED****1,5xd****PLUG**

1623144	Ø	P	L	l1	d	Limit	□	●Ø
16231441010419	#4	40	2.00	.69	.1410	H2	.110	43
16231441010427	#6	32	2.38	.88	.1940	H3	.152	36
16231441010435	#8	32	2.38	.94	.2200	H3	.165	#29
16231441010438	#10	24	2.50	1.00	.2550	H2	.191	25
16231441010451	1/4"	20	2.72	1.13	.3180	H3	.238	#7
16231441010458	5/16	18	2.94	1.25	.3810	H3	.286	F
16231441010466	3/8"	16	3.38	1.66	.3670	H3	.275	5/16
16231441010474	7/16	14	3.59	1.66	.4290	H3	.322	U
16231441010482	1/2"	13	3.81	1.81	.4800	H3	.360	27/64

3 - 5 hls

